



Robotic Palletizer

Compact and adaptable

- Adaptable layout to production constraints
- Ability to handle multiple products simultaneously
- Up to 12 pallet magazine available
- Slip sheet and palet placement
- Low maintenance design
- Integrated industrial robot

SPECIFICATIONS:

Robot	Mitsubishi RV-70F
Speed	20 picks por minuto
Case size range	Length: 600mm
	Width: 600mm
	Height: 400 mm
	Custom sizes are available, please inquire.
Pallet size	Width: 1000 mm, Length: 1200 mm
Payload	Up to 50 kg
Stacking Height	1600 mm
Magazine Capacity	12 pallets
Finish	Epoxy coated steel mesh guarding and enclosure
Guarding	3-level security system, integrating Mitsubishi technology according to NOM IEC 61508 SIL3 and ISO 13849-1 Ple
	Perimeter security mesh with door interlock and curtains
Electrical	- Mitsubishi PLC Serie R
	- Mitsubishi HMI GOT 10in, color, touchscreen
	- Balluff distributed IO and sensors
	- NEMA 12 enclosures
Pneumatics	- SMC
Installation	Power: 230 VCA, 20 AMPS, 3 Phase. Control voltage: 24VDC. Air: 90 PSI. Temp: 0° a 40° C.
Options	Conveyor of entrance and exit.

Bld. Jaime Benavides Pompa 1039 col. Villas de nogalar
 25900 Ramos Arizpe, Coah.
 Tel: 01 844 430 9410
 www.nexonautomation.com